

MAX CYLINDER SIZING



Cap (Outside Diameter)	Cylinder Bore	Bore Options	Shaft Options	MAX Tube OD	MAX Cap OD	Bore Size [in]	Standard Base [A]	Spigot [B]	Standard Piston [C]	Head [D]	Shaft Exterior [E]
		2.5" BORE, 5/16" WALL (TUBE O.D 79.4MM)	<ul style="list-style-type: none"> • 1.25" SHAFT • 1.5" SHAFT 	79.4mm	95mm	63.5mm (2 1/2")	16mm	5mm	62mm (49mm)	62mm	12mm
		3" BORE, 3/8" WALL (TUBE O.D 96MM)	<ul style="list-style-type: none"> • X1.5" SHAFT • X1.75" SHAFT • X2" SHAFT 	95.25	115mm	76.2mm (3")	20mm	5mm	69mm	82mm	15mm
		3.5" BORE, 3/8" WALL (TUBE O.D 108MM)	<ul style="list-style-type: none"> • X1.75" SHAFT • X2" SHAFT 	107.9mm	130mm	88.9mm (3 1/2")	20mm	5mm	75mm	90mm	15mm
		4" BORE, 1/2" WALL (TUBE O.D 127MM)	<ul style="list-style-type: none"> • (X2" SHAFT) • X2.5" SHAFT 	127mm	152.4mm	101.6mm (4")	25mm	5mm	(75mm) 94mm	102mm	20mm
		5" BORE, 5/8" WALL (TUBE O.D 159MM)	<ul style="list-style-type: none"> • X2.5" SHAFT • X3" SHAFT 	158.75mm	188mm	127mm (5")	35mm	8mm	105mm	127mm	20mm
		6" BORE, 3/4" WALL (TUBE O.D 190MM)	<ul style="list-style-type: none"> • 3" SHAFT • 3.5" SHAFT • 4" SHAFT 	190.5mm	215mm	152mm (6")	40mm	10mm	135mm	152mm	25mm